

[Text on drawings.]

ERSATZBLATT (REGEL 26) = REPLACEMENT SHEET (RULE 26)

[search report in English and in German]

TRANSLATION ACES

29 Broadway ◆ Suite 2301

New York, NY 10006-3279

Tel. (212) 269-4660 ◆ Fax (212) 269-4662



AFFIDAVIT OF ACCURACY

STATE OF NEW YORK)
) ss.:
COUNTY OF NEW YORK)

I, the undersigned, being duly sworn, depose and state:

I am qualified to translate from the German language into the English language by virtue of being conversant with these languages and, furthermore, having translated professionally from German into English for more than 10 years;

I have carefully made the translation appearing on the attached and read it after it was completed; and said translation is an accurate, true and complete rendition into English from the original German -language text, and nothing has been added thereto or omitted therefrom, to the best of my knowledge and belief.

TRANSLATION ACES, INC.

Subscribed and sworn to before me

this 26 day of January, 2007.

KARYN L. TASENS
Notary Public, State of New York
No. 31-4680695
Qualified in New York County
Commission Expires Oct. 31, 2010



[Translation from German]

Printed 28 Mar. 2006 CLMSPAMD PCT/EPO4/12779

Eisenführ, Speiser & Associates
Hamburg, 23 March 2006

Our reference: SH 414-02WO FM/ath
Direct dial: 040/309 744 34

Applicant/Owner: SOLUTIONS Branding & Design Companie GmbH & Co. KG
Official serial No.: PCT/EP 2004/012779

New Claim 1

1. Instrument (20) for pulling ticks out of the skin of animals or humans, comprising:
a longitudinal grip piece (21) for gripping the instrument (20) and
an end piece (4), which is at least partially flattened, having, at least in part, a first slot
(24) for gripping the tick, which end piece (4) terminates in an essentially fork-like shape having at
least two prongs (6), between which a space (10) is formed for grasping a tick, characterized in
that the grip piece (21) has a second slot (22) in order to permit the space (10) between the
prongs (6) of the end piece (4) to be varied, where the slots (22, 24) are connected together by a
film hinge, where by compression of the grip piece (21) the slot (22) and thus, via the film hinge
(26), the slot (24) can also be compressed, hence the space (10) between the prongs narrowed
and, lastly, the tick grasped in this way.

...ved at the EPO on Mar. 23, 2006 12:04:49.

AMENDED SHEET 23 Mar 2006